

KLICK LIGHTING CONTROL SYSTEM

The comprehensive Klik range offers a quick and easy way to control lighting in ceiling voids

SPECIFICATION

- Compact - allows installation in confined spaces
- Mains terminal capacity 5 x 4mm²
- Mains terminal rated at 16 Amps
- Sockets rated at 6 Amps
- Complies with BS 5733



CEILING DISTRIBUTION BOXES

Part No.	Description	Code
KLDS4	4 Ways	4011
KLDS6	6 Ways	4012
KLDS8	8 Ways	4013
KLDS10	10 Ways	4015
KLDS12	12 Ways	4016

SPECIFICATION

- 3 pin plugs have terminations for live, neutral and earth and are suitable for use with any Klik lighting or Klik AX sockets and Klik KLDS
- 4 pin plugs have terminations for live, neutral, earth and auxiliary and are suitable only for use with Klik AX sockets and Klik KLDS



6A PLUGS

Part No.	Description	Code
White		
P22	3 Pins	4019
P64AX	4 Pins	4020
Red		
P64AXR RED	4 Pins	4020

SPECIFICATION

- Ceiling roses pre-wired with heat resisting PVC flexible cord, complying with BS 6500



6A PRE-WIRED CEILING ROSES

Part No.	Description	Code
PCR2000/2.0	2m Cord, 3 Pin	4041
PCR2000/3.0	3m Cord, 3 Pin	4056
CR64AX/2.0	2m Cord, 4 Pin	4076
CR64AX/3.0	3m Cord, 4 Pin	4077
CR64AX/4.0	4m Cord, 4 Pin	4077

SPECIFICATION

- PCR2000: Plug has 3 terminations live, neutral and earth. Socket has 4 terminations live, neutral, earth and loop in
- CR64AX: Plug has 4 terminations live, neutral, earth and auxiliary. Socket has 5 terminations live, neutral, earth, auxiliary and loop in



6A PLUG-IN CEILING ROSES

Part No.	Description	Code
PCR2000	3 Pin	2760
CR64AX	4 Pin	2761

SPECIFICATION

- Size: 85mm dia. x 31mm deep
- Fixings: 50.8mm standard diagonal (BESA)
- Complies with BS 5733



MOUNTING BOXES

Part No.	Description	Code
MB2	Mounting Boxes	4017

SPECIFICATION

- Plugs pre-wired with heat resisting PVC flexible cord, complying with BS 6500



6A PRE-WIRED PLUGS

Part No.	Description	Code
White Plug with 0.75mm² Flex		
P22/2.0	2m Cord, 3 Pins	4033
P22/3.0	3m Cord, 3 Pins	4033
P22/4.0	4m Cord, 3 Pins	4033
White Plug with 1mm² Flex		
P22/1.0PVC/3	3m Cord, 3 Pins	4033
P22/1.0PVC/5	5m Cord, 3 Pins	4033
P64AX/1.0PVC/5	5m Cord, 4 Pins	4035
Red Plug with 0.75mm² Flex		
P64AXR/3.0	3m Cord, 4 Pins	4035
P64AXR/4.0	4m Cord, 4 Pins	4035
Red Plug with 1mm² Flex		
P64AXR1.0PVC/5	5m Cord, 4 Pins	4035

IDEAL FOR

- Shops
- Warehouses
- Malls
- Offices
- Recessed Ceilings