




DOWNLIGHT & GROUNDLIGHT KITS

All fibre optic kits provide an easy-install, low maintenance solution to lighting almost any location. With no heat or electricity carried in the cables or end fittings, they are safe for use even in damp and humid areas. With the flexibility of static white light or continuous colour change, fibre optic lighting can enhance any environment.

75W SPECIFICATION

- 75w tungsten halogen lightsource
- Fitted with a 6 colour colourwheel
- Separate power feed to colourwheel allows for continuous colour change or static colour
- Dimensions: A=261mm, B=140mm, C=119mm



Cutout required for fittings 28mm


FIBRE OPTIC GROUND KITS

Part No.	Description	Code
FO-MFK6-	** 75W, tails 2.0-3.0m, 6 x 35mm stainless steel pavers, 6 colour colourwheel with separate feed	8663
FO-MFK10-	** 75W, tails 2.0-5.6m 10 x 35mm stainless steel pavers, 6 colour colourwheel with separate feed	8663

Suffix -FR for frosted glass in fittings

Suffix -CL for clear glass in fittings

**Requires 2 x separately switched 240v supplies/sockets



IDEAL FOR: ■ Bathroom uplighting ■ Stairways ■ Decks / Patios ■ Hallways ■ Bedrooms ■ Sauna uplighting

100W SPECIFICATION

- 100w tungsten halogen lightsource
- Fitted with a 6 colour colourwheel
- Separate power feed to colourwheel allows for continuous colour change or static colour
- Dimensions: A=261mm, B=140mm, C=119mm



Cutout required for fittings 16mm

FIBRE OPTIC SUBMERSIBLE KITS


Part No.	Description	Code
FO-SPK6-	** 100W, tails 3.0-4.0m, 6 x 21mm stainless steel spa fittings, 6 colour colourwheel with separate feed	8664

**Requires 2 x separately switched 240v supplies/sockets

IDEAL FOR: ■ Underwater lighting in spas & baths ■ Water features ■ Sauna lighting

100W SPECIFICATION

- 100w tungsten halogen lightsource
- Fitted with a 6 colour colourwheel
- Separate power feed to colourwheel allows for continuous colour change or static colour
- Dimensions: A=261mm, B=140mm, C=119mm



Cutout required for fittings 40mm

FIBRE OPTIC DOWNLIGHT KITS

Part No.	Description	Code
FO-CWD8-	** 100W, tails 2.0-5.0m, 8 x recessed eyeball fittings, directional and focusable, 6 colour colourwheel with separate feed	8662

Suffix -FW for white fittings

Suffix -FB for black fittings

**Requires 2 x separately switched 240v supplies/sockets

IDEAL FOR: ■ Bathroom downlighting ■ Bedrooms - decorative wall wash ■ Display lighting ■ Low level ambient lighting

LIGHTSOURCE DIMENSIONS:

