

T8 BATTENS



IP20

T8 FLUORESCENT BATTENS

A comprehensive range of Fluorescent Battens and Accessories to ensure the light from the single or twin tubes is effective in residential through to commercial and Industrial applications. High quality powder coated paint finish with smooth edges. Colour matched injection moulded end caps with alignment pins for continuous mounting.

SECTOR

SECTORPACK II HIGH FREQUENCY BATTENS

Part No.	Description	Code
Single High Frequency		
SBF4136HF	4Ft 1.2m 1 x 36WT8	4106
SBF5135T5	5Ft 1.5m 1 x 35WT5	5815
SBF5149T5	5Ft 1.5m 1 x 49WT5	5815
SBF5158HF	5Ft 1.5m 1 x 58WT8	4108
SBF6170HF	6Ft 1.8m 1 x 70WT8	4110
Single High Frequency Emergency - Maintained		
SBF4136HF E3	4Ft 1.2m 1 x 36WT8	4120
SBF5158HF E3	5Ft 1.5m 1 x 58WT8	4122
SBF6170HF E3	6Ft 1.8m 1 x 70WT8	4124
Twin High Frequency		
SBF4236HF	4Ft 1.2m 2 x 36WT8	4112
SBF5258HF	5Ft 1.5m 2 x 58WT8	4114
SBF6270HF	6Ft 1.8m 2 x 70WT8	4116
Twin High Frequency Emergency - Maintained		
SBF4236HF E3	4Ft 1.2m 2 x 36WT8	4121
SBF5258HF E3	5Ft 1.5m 2 x 58WT8	4123
SBF6270HF E3	6Ft 1.8m 2 x 70WT8	4125

SECTORPACK II SINGLE SWITCH START BATTENS

Part No.	Description	Code
Switch Start		
SBF2118	2Ft 0.6m 1 x 18W	1443
SBF4136	4Ft 1.2m 1 x 36W	4044
SBF5158	5Ft 1.5m 1 x 58W	4045
SBF6170	6Ft 1.8m 1 x 70W	4046
SBF81100	8Ft 2.4m 1 x 100W	4047
Switch Start Emergency - Maintained		
SBF4136 E3	4Ft 1.2m 1 x 36W	4094
SBF5158 E3	5Ft 1.5m 1 x 58W	4096
SBF6170 E3	6Ft 1.8m 1 x 70W	4098



SECTORPACK II TWIN SWITCH START BATTENS

Part No.	Description	Code
Switch Start		
SBF2218	2Ft 0.6m 2 x 18W	4048
SBF4236	4Ft 1.2m 2 x 36W	4049
SBF5258	5Ft 1.5m 2 x 58W	4050
SBF6270	6Ft 1.8m 2 x 70W	4051
SBF82100	8Ft 2.4m 2 x 100W	4052
Switch Start Emergency - Maintained		
SBF4236 E3	4Ft 1.2m 2 x 36W	4110
SBF5258 E3	5Ft 1.5m 2 x 58W	4102
SBF6270 E3	6Ft 1.8m 2 x 70W	4104



SPECIFICATION

- Integral High Frequency control gear provides instant start with longer lamp life and energy savings of up to 20%
- Also High Energy and Efficiency T5 lamp options
- Flicker free operation independent of mains voltage fluctuations also provides reliable operation and long service life
- Triphosphor colour 840 Fluorescent tubes included in HF battens and halophosphate white included in switch start battens
- Integral emergency versions are 3 hour maintained



DIMENSION TABLE (mm):

Single	L	W	C	H
2ft	627	58	525	92
4ft	1238	58	605	92
5ft	1538	58	605	92
6ft	1802	58	605	92

Twin	L	W	C	H	W2
2ft	627	58	525	92	89
4ft	1238	58	605	92	89
5ft	1538	58	605	92	89
6ft	1802	58	605	92	89