

LED MODULES



LED MODULES

These compact modules offer a great opportunity to replace ordinary 50mm and 111mm lamps with professional high power LED. Separate LED driver required. Useful life in excess of 50,000 hours. All feature incorporated Heatsink for greater heat dissipation and run at a fraction of the cost of conventional lighting.

50MM (MR16) 3 x 1W

Part No.	Description	Code
LED-MD53S	3W alu. 10° spot light	3995
LED-MD53F	3W alu. 50° flood light	3995
LED-A1PP1M	1M Plug 'n' Play Extension & Connection Lead	7820

Suffix:
C/W = Cool White
W/W = Warm White
BLU = Blue

■ 1 - 3 per driver



50MM (MR16) 3 x 3W

Part No.	Description	Code
LED-MD59S	9W alu. 10° spot light	3995
LED-MD59F	9W alu. 50° flood light	3995
LED-A1PP1M	1M Plug 'n' Play Extension & Connection Lead	7820

Suffix:
C/W = Cool White
W/W = Warm White
BLU = Blue
N/W = Natural White

■ 1 - 3 per driver




111MM (AR111) 7 X 3W

Part No.	Description	Code
LED-MD121S	21W alu. 10° spot light	4005
LED-MD121F	21W alu. 45° flood light	4005

Suffix:
C/W = Cool White
W/W = Warm White


■ Supplied with LED driver

240V




SPECIFICATION

- Aluminium construction
- Requires Plug 'n' Play connectors for wiring to driver
- Provides light output more than 35W GU10



SPECIFICATION

- Aluminium construction
- Requires Plug 'n' Play connectors for wiring to driver
- Provides light output more than 50W GU10 at more than 40 lumens per watt



SPECIFICATION

- Replaces AR111 lamps for cool touch long life display light
- Features 7 x 3W high power LEDs
- High colour render index

■ Bespoke LED-DLT cast tilt aluminium fittings available

IDEAL FOR

- Kitchens
- Leisure Centres & Retail Areas
- Bars, Pubs and Clubs
- Cafe's
- Exhibition spaces
- Not suitable for fire rated downlighters (see pages 29 & 30)

■ Series LED drivers see opposite

