

T5 DIRECT/INDIRECT LUMINAIRES

ISO DROP BASKET AND ISO SEMI RECESSED

A comprehensive range of T5 direct/indirect luminaires designed to aid LG3 2001/LG7 compliance. Providing contemporary design for specifications where style is of equal importance as technical performance.



IP20



ISO DB DROP BASKET

Part No.	Description	Code
LAY IN - Specular Cat 2 Louvre		
ISOL314C2	3x14W T5 HE	5886
ISOL414C2	4x14W T5 HE	5886
LAY IN - Semi Specular Cat 2 Louvre		
ISOL314SSC2	3x14W T5 HE	5886
ISOL414SSC2	4x14W T5 HE	5886
PULL UP - Specular Cat 2 Louvre		
ISO314C2	3x14W T5 HE	5886
ISO414C2	4x14W T5 HE	5886
PULL UP - Semi Specular Cat 2 Louvre		
ISO314SSC2	3x14W T5 HE	5886
ISO414SSC2	4x14W T5 HE	5886
SPRING TEE - Specular Cat 2 Louvre		
ISOT314C2	3x14W T5 HE	5886
ISOT414C2	4x14W T5 HE	5886
SPRING TEE - Semi Specular Cat 2 Louvre		
ISOT314SSC2	3x14W T5 HE	5886
ISOT414SSC2	4x14W T5 HE	5886



SPECIFICATION

- The ISO Drop basket is the answer to single luminaire compliance to CIBSE LG3 2001/LG7 and BSEN 12464
- Achieves required levels of light directed back onto ceiling and walls
- Supplied with High Efficiency 14W T5 Colour 840 lamps
- High quality powder coated steel body and perforated side baskets
- A choice of 2 central louvres retained with shoot bolts for easy lamp change
- LG3 2001 Specifications. Semi Specular will offer luminance levels below 1500 cd/m² above 65°
- BSEN 12464 Compliance. Specular will offer luminance levels below 1000 cd/m² above 65°

ISO SR SEMI RECESSED

Part No.	Description	Code
LAY IN - Specular Cat 2 Louvre		
ISOLSR240C2	2x40W TCL	5886
ISOLSR255C2	2x55W TCL	5886
ISOLSR414C2	4x14W T5 HE	5886
LAY IN - Semi Specular Cat 2 Louvre		
ISOLSR240SSC2	2x40W TCL	5886
ISOLSR255SSC2	2x55W TCL	5886
ISOLSR414SSC2	4x14W T5 HE	5886
PULL UP - Specular Cat 2 Louvre		
ISOSR240C2	2x40W TCL	5886
ISOSR255C2	2x55W TCL	5886
ISOSR414C2	4x14W T5 HE	5886
PULL UP - Semi Specular Cat 2 Louvre		
ISOSR240SSC2	2x40W TCL	5886
ISOSR255SSC2	2x55W TCL	5886
ISOSR414SSC2	4x14W T5 HE	5886



SPECIFICATION

- The ISO Semi Recessed shallow drop basket provides greater harmonisation with its intended environment together with enhancing horizontal light distribution
- Used with ISO Wall and ISO Surface luminaires it can achieve compliances with LG3 2001/LG7
- T5 version Supplied with High Efficiency 14W Colour 840 lamps
- TCL Versions require lamps
- High quality powder coated steel body and perforated side baskets
- A choice of 2 central louvres retained with shoot bolts for easy lamps change, Specular and Semi Specular Category 2

Suffix:
 E3 = 3 Hour Maintained Emergency Pack (Integral)
 HFR = Dimmable (Analogue 1-10V)
 SD = Switch Dim
 DDC = Digital Dimming Control

