

EXTERNAL CIRCULAR UTILITY



COOLINE IP65

The cooline IP65 is designed for use where aesthetics of the lighting scheme and robust construction are paramount. Louvre and eyelid versions reduce upward glare and provide greater directional emphasis of lumination to architectural and design environments.



IP65

LOUVRED BEZEL MINI

Part No.	Description	Code
UTIPL16275BKO	16W Black Opal Sw/Start	4411
UTIPL16275WOHF	16W White Opal HF	4411
UTIPL16275GOHF	16W Graphite Opal HF	4411

LOUVRED BEZEL MISTI

Part No.	Description	Code
UTIPL28350BKO	28W Black Opal Sw/Start	4412
UTIPL28350WOHF	28W White Opal HF	4412
UTIPL28350GOHF	28W Graphite Opal HF	4412
UTIPL28350GOPC	28W Gr/Op+Photocell	4412
UTIPL28350WOHFE3	28W WH/Op E3	4422

EYELID BEZEL MINI

Part No.	Description	Code
UTIPE16275BKOHF	16W Black Opal HF	4411
UTIPE16275WOHF	16W White Opal HF	4411
UTIPE16275GOHF	16W Graphite Opal HF	4411

EYELID BEZEL MISTI

Part No.	Description	Code
UTIPE28350BKOHF	28W Black Opal HF	4412
UTIPE28350WOHF	28W White Opal HF	4412
UTIPE28350GOHF	28W Graphite Opal HF	4412

PLAIN BEZEL MINI

Part No.	Description	Code
UTIPIB16275BKOHF	16W Black Opal HF	4411
UTIPIB16275WOHF	16W White Opal HF	4411
UTIPIB16275GOHF	16W Graphite Opal HF	4411

PLAIN BEZEL MISTI

Part No.	Description	Code
UTIPIB28350BKOHF	28W Black Opal HF	4412
UTIPIB28350WOHF	28W White Opal HF	4412
UTIPIB28350GFHF	28W Graphite Fresnel HF	4412

SUFFIX TABLE:

Control Gear Options:

(Switch Start as Standard)

- HF = High frequency control gear
- HF E3 = Integral emergency version (must be HF)
- PC = Factory fitted photocell

Bases:

- W = White, BK = Black, G = Graphite
- UTHPD = Diecast aluminium base


Diffusers:

- O = Opal, F = Fresnel



SPECIFICATION

- BC cap (100W max) option available in mini
- Complete with energy saving 2D lamps GE branded colour 827 28W 2D 4 Pin
- Robust polycarbonate body and diffuser
- Switch Start PFC, High Frequency (HF) and High Frequency 3hr Emergency (HF E3) Options available
- Sparked polycarbonate diffuser is detained by screw down polycarbonate retaining bezel
- Anti Tamper Screws Available
- Photocell Version (external use only)
- Simple Installation with besa entries
- Available in Black, White and Graphite Finish
- Dia cast metal base option (with polycarbonate bezel)



DIMENSION TABLE (MM)

Fitting	Diameter	Depth
Mini	283	103
Midi	353	110



Cooline IP65 now offers a clear fresnel lens diffuser which offers superior light output.



Die cast metal base option with multiple side cable entry.