

COOLINE LED



IP21

The Cooline LED provides long life, reduced maintenance requirements and energy efficient operation. LED technology provides the latest solutions to lighting scheme and environmental demands. See Cooline data (page 56) for additional product specification

LED SPECIFICATION

- Prismatic polycarbonate diffuser only
 - Life 50,000 hours (5 x the life of fluorescent lighting)
 - Maintenance free operation
 - Fit and forget for life of product 16.5yrs @ 3000hrs per year
 - Energy efficient
 - Instant light
 - Unlimited switching
 - No UV emitted by LEDs
 - 100-265V~50/60Hz (input voltage can be customized on request)
- LED12
LED18
LED24
Cool-white 6500k typ. CRI 70
Natural-white 4100k typ. CRI 75
Warm-white 3100k typ. CRI 80
Cool white provides optimal LED performance



COOLINE LED MIDI

Part No.	Description	Code
UT-425WP/LED18CW1	18 LED White Pris	8520
UT-425WP/LED18CW1E3	18 LED White Pris E3	8521

See **SUFFIX TABLE** for all variants

COOLINE LED MAXI

Part No.	Description	Code
UT-525WP/LED24CW1	24 LED White Pris	8520
UT-525WP/LED24CW1E3	24 LED White Pris E3	8521

See **SUFFIX TABLE** for all variants

SUFFIX TABLE:

LED Options:

LED12 = 12 X LED 1 watt high power
LED18 = 18 X LED 1 watt high power
LED24 = 24 X LED 1 watt high power
CW1 = Coolwhite
NW1 = Natural White
WW1 = Warm White

E3 = 3 hour integral emergency

Bases: W = White, B = Brass, C = Chrome, A = Aluminium

COOLINE ANTI LIGATURE



IP21

The Cooline Profile Anti Ligature is a smooth, close fitting luminaire. Ideal for installations requiring high levels of security e.g. Prisons, Hospitals and Schools
See above COOLINE LED specification for LED details+ LED suffix options


SPECIFICATION

- Anti-ligature aluminium body
- Vandal resistant screw-down polycarbonate diffuser in a choice of clear prismatic or white opal
- Tamper proof fixings (chrome or white)
- Spun Aluminium base and trim
- Many body and lamp options available, sharing the other features of the Cooline range
- For use with anti-pick mastic
- Lamp access from front



The unit can be wall or ceiling mounted and should be used in conjunction with anti-pick mastic

For installation and lamp maintenance the front trim can be easily removed by means of loosening the six anti-vandal captive screws



MINI COOLINE PROFILE

Part No.	Description	Code
UT-PRO16232WO	16W White Opal	8516
UT-PRO16232APD HF	16W Alu Pris.	8516

See **SUFFIX TABLE** for all variants

MIDI COOLINE PROFILE

Part No.	Description	Code
UT-PRO28465WO	28W White Opal	8528
UT-PRO38465APD HF	38W Alu Pris.	8538

see **SUFFIX TABLE** for all variants

MAXI COOLINE PROFILE

Part No.	Description	Code
UT-PRO38595WO	38W White Opal	8528
UT-PRO55595APD HF	55W Alu Pris.	8538

See **SUFFIX TABLE** for all variants

MAXI COOLINE PROFILE LED

Part No.	Description	Code
UT-PRO595WP/LED18CW1	18LED Wht Pris.	8520
UT-PRO595WP/LED24CW1	24LED Wht Pris.	8520

See **SUFFIX TABLE** for all variants

DIMENSION TABLE (MM)

Fitting	Diameter	Depth
Mini	250	102
Midi	434	106
Maxi	524	112